

LINDA BARKER PAINTS

PRODUCT ADVICE

ULTRA MATTE WALLPAINT

Where to use:

For interior walls and ceilings – sheen level 2.5% means the flattest possible matt – maximum opacity & exceptional depth of colour - this is a super Matte wallpaint

Availability:

In 2.5L and 5L cans in all 90 colours plus colour matching.

Coverage: Up to 60 m² per 5 litres/per coat – normally 2 coats needed.

Drying time: Touch dry in 1 – 2 hours, recoat after min 4 hours.

Sheen level: 2.5%

Preparation:

Surfaces should be sound, clean, dry and free from grease. Prime bare plaster & plasterboard with a plaster-sealer or a water-diluted mist coat of this paint – approx 15% water addition. Seal fillers first.

Painting:

Do not paint in temperatures below 5°C or direct sunlight or excessive heat above 30°C.

Please check for correct product and colour prior to use as we will not be held liable for issues caused as a result of an incorrect colour or product being applied. Our limit of liability does not exceed the value of our product.

Stir thoroughly before use.

DO NOT THIN. Apply with a good quality medium pile roller. Do not layoff – always keep a wet edge. Do not go back over painted areas. Do not over spread. Best results are normally achieved with two coats.

Clean up: equipment with warm soapy water.

Maintenance

Wipe gently with a clean wetted lint-free damp cloth or sponge – no detergent etc.

Storage:

This product is water based and must be protected from frost and extreme temperatures. Use within 12 months of purchase. We accept no responsibility for the deterioration of contents or packaging after this.

Disposal: Though water based, please do not dispose of into watercourse. Waste materials must be disposed of in accordance with the Environmental Protection Act 1990 and relevant regulations made thereunder. For further information contact the Environment Office at your local council.

Easicolor Ltd, 44 leighton beck rd, LA77AX

Health & Safety:

Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water.
Skin - wash off with water. Keep out of reach of children.

VOC content max 0.1g/L

Safety Data Sheets are available on request.